

# COMBILIFT

**Customized Handling Solutions** 

## C10,000L

**Customized Handling Solutions** 



Lumber Box



Optional Chainsaw Box











three machines in one


counterbalance forklift > aisle truck > side loader

### Model C10,000L




#### SIDEWAYS MODE





FORWARD MODE




#### **COMBILIFT Ltd**

Co.Monaghan, Ireland **Tel:** 011 353 47 80500 **Fax:** 011 353 47 80501

#### **COMBILIFT USA**

303 Concord Street, Greensboro North Carolina 27406 **Toll Free:** 1-877 COMBI 56

Tel: 336-378-8884 Fax: 336-378-8842 info@combilift.com



REF	DESCRIPTION	C10,000L
la	Max. Lift Height	159"
lb	Free Lift Height	0"
2	Height Mast Closed	117"
3	Max.(Mast raised)	198"
4	Overall Length	981/2"
5	Mast Travel	49"
6	Ground Clearance Under Mast	11"
7	Ground Clearance to Centre of Wheelbase	10½"
8	Height Over Cab or of Overhead Guard	102"
9	Width with Standard Door	88"
10	Outside Spread of Fork Arms	53"
11	Track Front	79"
12	Frame Opening	55"
13	Load Centre Distance	24"
14	Overhang Front	12"
15	Wheel Base	80"
16	Overhang Back	6"
17	Length From Face of Fork	51"
18	Approach Angle	45°
19	Ramp Angle	29°
20	Departure Angle	45°
21	Forward Tilt	3°
22	Backward Tilt	5°
23	Minimum Outside Radius	77"
24	Platform Height	26¾"
25	Platform Length	471/2"
Α	Capacity	10,000lbs
В	Unladen Weight	15,200lbs
С	Maximum Ground Speed	10mph
D	Gradibility	15%
E	V2003 T Kubota Diesel/3ltr. GM LPG	59HP/65HP
F	Electrics	12 Volt
G	Fork Section	8" x 1½" x 47½"
Н	23 x 10 - 12 Front Tyre	OD 23" / Width 10"
1	28 x 12.5 - 15 Rear Tyre	OD 28" / Width 11"
J	Standard Colour	Green and Grey
K	Suspension Seat	KAB Model 116

#### FEATURES INCLUDE:

- Rubber Mounted Half Open Cabin
- Multi-Direction Operation
- 3 Wheel Hydrostatic Drive
- · Load Sensing Steering
- 4 Way lever Positioning of Wheels
- Hydraulic Oil Cooler

**Distributed By** 

www.COMBiLiFT.COM